

## ADSPRAY™ 1000/1500DEC

### HOT WATER PRESSURE WASHERS

Nothing cleans like a pressure washer. And when you add hot water to the job, the cleaning effect is even greater.

The *AdSpray 1000DEC* and *1500DEC* Pressure Washers have diesel-fueled water heaters that heat source water as much as 140° F (60° C) for additional cleaning power. And they're cart-mounted, so you can bring them right to the cleaning site.

In addition to hot water, these machines also bring adjustable pressure to bear on the cleaning job. The model *1000DEC* delivers three gallons per minute (11.3 l./min.) at up to 1000 p.s.i. (69 bar), and the model *1500DEC* delivers three and a half gallons per minute (13.25 l./min.) at up to 1500 p.s.i. (103.4 bar).

The pump that delivers this kind of performance features long-life ceramic plungers, and has filter as well as mechanical thermal valve protection. It's covered by a five-year warranty.

These are both high performers when it comes to economy too. The *AdSpray 1000DEC* and *1500DEC* are functional, no-frills, labor-savers that can fit into a tight cleaning equipment budget.

As with other Advance brand pressure washers, there are a variety of accessories available to meet special cleaning needs.



#### Comes With:

- 40' (12 m) hose
- Wand with Multi-Reg tip

To maintain the peak performance of your floor maintenance equipment, buy only genuine **apa** parts and accessories.

# S P E C I F I C A T I O N S



The *AdSpray 1000DEC* and *1500DEC* have a dependable plunger-type pump with mechanical thermal relief valve, for a long life with few repairs, and greater cleaning productivity even with extended periods of use.



Safety on/off switch for the burner and the pump are easily accessible.



The fuel tank cap is easy to get at, making it easy to fill. Both the diesel fuel tank and the heater coil shroud are stainless steel, for durability and good looks.



The spray gun has on/off spray control with insulated handle and two-piece insulated wand. Spray nozzle adjusts from 0-60° with high/low adjustment for soap application. Spray pressure is adjustable.

	Model 1000DEC	Model 1500DEC
<b>Motor:</b>	2 hp, 115 v/60 Hz	3 hp, 220 v/60Hz
<b>Power Cord:</b>	35' (10.6 m) w/g.f.i.	35' (10.6 m) w/g.f.i.
<b>Pump:</b>	Pump features on both models include teflon graphite seals, ceramic-coated steel pistons, stainless steel valves, aluminum head, mechanical thermal relief valve, ceramic plunger and by-pass running against a closed gun.	
<b>Output (adjustable):</b>	1000 p.s.i. (69 bar) 3 g.p.m. (11.3 liters/min.)	1500 p.s.i. (103.4 bar) 3.5 g.p.m. (13.25 liters/min.)
<b>Chemical Injection:</b>	Variable rate, after the pump on both models	
<b>Water Heater:</b>	Both models feature a 230,000 b.t.u., diesel-fueled Beckett burner, with continuous blower. Heats water as much as 140° F (60° C) over inlet temperature. Has temperature limit switch and pressure relief.	
<b>Fuel Tank:</b>	2.5 gallon (9.5 liter) capacity, stainless steel tank, both models (diesel fuel)	
<b>Gun/Wand:</b>	Both models have insulated grip, with on/off trigger handle. Multi-jet tip is adjustable 0–60° spray pattern, and high/low adjustment for soap application.	
<b>Pressure Hose:</b>	40' (12 m) non-marking w/quick-disconnect	40' (12 m) non-marking w/quick-disconnect
<b>Construction:</b>	Both models built on 1 ½" (38 mm) tubular steel frame cart with 10" (25 cm) diameter heavy-duty transport tires	
<b>Dimensions:</b>	42" (106.7 cm) high 24 ¼" (61.6 cm) wide 42" (106.7 cm) long	42" (106.7 cm) high 24 ¼" (61.6 cm) wide 42" (106.7 cm) long
<b>Weights:</b>	300 lbs. (136 kg) net 350 lbs. (159 kg) shipping	300 lbs. (136 kg) net 350 lbs. (159 kg) shipping

All specifications subject to change without notice.

## Product Part Numbers:

*AdSpray 1000DEC* — 100 709

*AdSpray 1500DEC* — 100 710



Nilfisk-Advance, Inc.  
14600 21st Avenue North  
Plymouth, MN, 55447-3408  
www.nilfisk-advance.com  
Phone: 800-989-2235  
Fax: 800-989-6566

Nilfisk-Advance Canada Company  
396 Watline Avenue  
Mississauga, Ontario, Canada, L4Z 1X2  
www.nilfisk-advance.com  
Phone: 800-668-8400 or 905-712-3260  
Fax: 800-263-5111 or 905-712-3255

©1998, Nilfisk-Advance, Inc., Form L0784A, 11/98 Printed in U.S.A.